



## **DRIVEGUARD™ Chuckhole Cold Patch**

A carefully prepared blend of finely graded mineral aggregate and specially prepared asphalt. Ready to use from the bag, it affords quick and economical repair of chuckholes in any asphalt or concrete surface. **Chuckhole Cold Patch** sticks to asphalt and concrete without a primer even in cool, wet weather. Special packaging provides a shelf life of up to two years.

### **Uses**

- Chuckhole repair of any asphalt or concrete surface.

### **Advantages**

- Professional Quality - same material used by many state and local highway departments and contractors.
- All Weather - use wet or dry. Winter and summer grades available.
- Easy to Use - apply directly from heavy duty plastic bag.

## **INSTALLATION**

### **Surface Preparation**

- Sweep chuckhole clean of all dirt, dust, and debris. Remove loose pavement fragments from edges of area to be patched. Take care to keep vertical edges of chuckholes as clean as possible.

### **Application**

- Pour or shovel into chuckhole. Level material slightly higher than desired depth to allow for compaction. Compact with flat side of shovel, tamper or roller.

### **Restrictions**

- Do not use over mud or clay. Material works best over a solid base.
- Do not use where material, once applied, may come in contact with potable water. Exterior use only.
- Keep bag tightly sealed when not in use.

**Cautions**

- Causes eye irritation. Inhalation of vapors can be harmful to upper respiratory tract and central nervous system. Keep away from heat or flame. Wear eye and skin protection when handling. Avoid prolonged or repeated breathing of vapors, mists, or fumes. Do not take internally. Observe good hygiene and safety practices when handling this product. **KEEP OUT OF REACH OF CHILDREN!** Use only with adequate ventilation. Seal bag when not in use. **FOR EXTERIOR USE ONLY.**

**PACKAGING INFORMATION**

<u>Product Number</u>	<u>Size</u>	<u>Quantity</u>	<u>Weight</u>
51850	Bag	Each	50 lbs.
51860	5 Gal.	Each	73 lbs.